

GoRugged R2000 Dual

Industrial Dual Module Cellular VPN Router with Power over Ethernet

For GSM/GPRS/EDGE/UMTS/WCDMA/HSPA+/LTE Networks

Robustel's R2000 Dual Industrial Dual Module Cellular VPN Router with Power over Ethernet provides fast and reliable communication for monitoring and controlling remote equipment. The added new feature, Power over Ethernet, makes installing or expanding much simpler and cheaper for both power and data transmission.

Key Features

- Embedded dual module supporting two SIM cards online simultaneously
- Four fast Ethernet LAN port supporting Power over Ethernet 12.95 W of POE/30 W of POE+ shared across the four LAN ports
- Supports Cellular, WAN, WLAN link backup and ICMP detection; also supports cold backup, warm backup and load balancing
- WAN - Static/PPPOE/DHCP Client
- Wi-Fi supporting AP mode and Client mode
- VPN tunnel - IPsec/OpenVPN/GRE/L2TP/PPTP/DMVPN
- Auto reboot via SMS/Timing
- Supports RobustLink (a centralized M2M management platform for remote monitoring, configuration and firmware upgrade)
- Management and upgrading via web user interface/ SMS/CLI/RobustLink
- Supports various APP like QoS, DDNS, VRRP, Captive Portal, SNMP, WLAN multi, multi-language
- Easy wall or DIN rail mounting options



Applications

- ATM/Vending Machine/Retail POS/Kiosks
- Branch Offices
- Convenience Stores
- Quick Service Restaurants
- Digital Signage
- IP Video Surveillance

Ordering Information

Model No.	Frequency Bands	Operating Environment
R2000-D3P1	Single module (Mini PCIe) WCDMA/HSDPA/HSUPA/HSPA+: 850/1900/2100 MHz GSM/GPRS/EDGE: 850/900/1800/1900 MHz	-40 to 70°C/5 to 95% RH
R2000-D3P2	Dual module (Mini PCIe) DC-HSPA+/HSPA+/HSPA/UMTS: 850/900/1900/2100 MHz GSM/GPRS/EDGE: 850/900/1800/1900 MHz	-40 to 70°C/5 to 95% RH
R2000-D4L1	Single module (Mini PCIe) FDD LTE: B1, B2, B3, B4, B5, B7, B8, B13, B17, B18, B19, B20, B21, B25, B28, B31 TDD LTE: B38, B39, B40, B41 DC-HSPA+/HSPA+/HSPA/UMTS: 850/900/1900/2100 MHz GSM/GPRS/EDGE: 850/900/1800/1900 MHz	-40 to 70°C/5 to 95% RH
R2000-D4L2	Dual module (Mini PCIe) FDD LTE: B1, B2, B3, B4, B5, B7, B8, B13, B17, B18, B19, B20, B21, B25, B28, B31 TDD LTE: B38, B39, B40, B41 DC-HSPA+/HSPA+/HSPA/UMTS: 850/900/1900/2100 MHz GSM/GPRS/EDGE: 850/900/1800/1900 MHz	-40 to 70°C/5 to 95% RH

GoRugged R2000 Dual

Industrial Dual Module Cellular VPN Router with Power over Ethernet

Specifications

Cellular Interface

- Standards: GSM/GPRS/EDGE/UMTS/WCDMA/HSPA/HSDPA/HSUPA/HSPA+/DC-HSPA+/LTE
- FDD LTE: max. 150/50 Mbps (DL/UL) @20M BW cat4
- TDD LTE: max. 100/50 Mbps (DL/UL)
- DC-HSPA+: 42/5.76 Mbps (DL/UL)
- HSPA+: max. 21.6/5.76 Mbps (DL/UL)
- WCDMA: 384/384 kbps (DL/UL)
- EDGE: 236.8 kbps (DL/UL)
- GPRS: 85.6 kbps (DL/UL)
- SIM: 2 (3 V & 1.8 V)
- Connector: SMA, female (2 x MAIN + 2 x AUX)

Ethernet Interface

- Number of ports: 1 x WAN and 4 x LAN (10/100 Mbps)
- Magnet isolation protection: 1.5 KV

WLAN Interface

- Standards: 802.11b/g/n, supporting AP and Client mode
- Data speed: 150 Mbps
- Frequency band: 2.412 - 2.485 GHz
- Security: WEP, WPA, WPA2
- Encryption: 64/128 AES, TKIP
- Connector: RP-SMA, female

Device Interface

- POE (4 x LAN)
Four ports power supply output
IEEE802.3 at/af standard compatibility
Maximum power output up to 30 W per port
Power management function
Voltage Range: 48 to 57V DC
- Digital Input (DI)
When router is used in in-vehicle networks, DI function makes router enter a state of low power consumption which can avoid the battery excessive consumption of the vehicle.

System

- 1 x Reset button
- LED indicators: 1 x RUN, 2 x PPP, 1 x USR, 2 x NET, 6 x RSSI

Contact:

www.robustel.com
info@robustel.com

Software

- Network protocols: PPP, TCP, UDP, DHCP, ICMP, NAT, DMZ, DDNS, VRRP, HTTP, HTTPS, DNS, ARP, SNTP, SSH, Telnet, SNMP, AAA etc.
- VPN tunnel: IPsec/OpenVPN/GRE/L2TP/PPTP/DMVPN
- Firewall: SPI, anti-DoS, Filter, Access Control
- Management: Web, SMS, CLI

Power Supply and Consumption

- Connector: 3.5 mm terminal block
- Input voltage: 9 to 48V DC
- Power consumption: Idle: 100 mA@12 V
Data link: 800 mA (peak)@12 V
- With ground screw

Physical Characteristics

- Housing & Weight: Metal, 750 g
- Dimensions: 145 x 130 x 46 mm
- Installations: Flat surface placement, wall mounting and 35 mm DIN rail mounting

Regulatory and Type Approvals

- Approvals & Certificates: CE, RCM
- EMC:
EMI: EN55022: 2006/A1: 2007 (CE & RE) Class B
EMS: IEC 61000-4-2 (ESD) Level 4
IEC 61000-4-4 (EFT) Level 4
IEC 61000-4-5 (Surge) Level 3

Package Contents

- 1 x Robustel R2000 Dual Industrial Dual Module Cellular VPN Router with Power over Ethernet
- 1 x Terminal block for power
- 1 x *Quick Start Guide* with download link of other documents or tools

Optional Accessories (sold separately)

- AC/DC power adapter
- POE power adapter
- SMA cellular antenna for 3G/4G LTE
- Stubby/magnet RP-SMA Wi-Fi antenna
- Wall mounting kit
- 35 mm DIN rail mounting kit